DOI: 10.2478/jwld-2014-0022

© Polish Academy of Sciences, Committee for Land Reclamation and Environmental Engineering in Agriculture, 2014 © Institute of Technology and Life Science, 2014

Available (PDF): www.itp.edu.pl/wydawnictwo; http://www.degruyter.com/view/j/jwld

Received18.07.2014Reviewed20.11.2014Accepted06.09.2014

- A study design
- **B** data collection **C** – statistical analysis
- \mathbf{D} data interpretation
- E manuscript preparation

 \mathbf{F} – literature search

Effectiveness of straw mulch on infiltration, splash erosion, runoff and sediment in laboratory conditions

Leila GHOLAMI^{1) ABCDEF}, Kazimierz BANASIK^{2) DEF}, Seyed Hamidreza SADEGHI^{3) AD}, Abdulvahed KHALEDI DARVISHAN^{3) ABCD}, Leszek HEJDUK^{2) DE}

¹⁾ Sari University of Agriculture and Natural Resources, Faculty of Natural Resources, P.O. Box 578, Sari, Iran.

²⁾ Warsaw University of Life Sciences – SGGW, Faculty of Civil and Environmental Engineering, ul. Nowoursynowska 159,

02-787 Warsaw, Poland; tel. +48 22 593 52 80, e-mail: kazimierz_banasik@sggw.pl

³⁾ Tarbiat Modares University (TMU), Faculty of Natural Resources, P.O. Box 46414-356, Noor, Iran

For citation: Gholami L., Banasik K., Sadeghi S.H., Khaledi Darvishan A., Hejduk L. 2014. Effectiveness of straw mulch on infiltration, splash erosion, runoff and sediment in laboratory conditions. Journal of Water and Land Development. No. 22 p. 51–60.

Abstract

Mulches have extraordinary potential in reducing surface runoff, increasing infiltration of water into the soil and decreasing soil erosion. The straw mulches as a biological material, has the ability to be a significant physical barrier against the impact of raindrops and reduce the detachment of soil aggregates. The present study is an attempt to determine the efficiency of straw mulch as conservation treatment in changes in the splash erosion, time-to-runoff, runoff coefficient, infiltration coefficient, time-to-drainage, drainage coefficient, sediment concentration and soil loss. The laboratory experiments have been conducted for sandy-loam soil taken from deforested area, about 15 km of Warsaw west, Poland under lab conditions with simulated rainfall intensities of 60 and 120 mm·h⁻¹, in 4 soil moistures of 12, 25, 33 and 40% and the slope of 9%. Compared with bare treatments, results of straw mulch application showed the significant enhancement effects on splash erosion, runoff coefficient, sediment concentration and soil loss and significant ($p \le 0.05$) correlation with r = -0.873, 0.873, 0.878 and 0.764 between rainfall intensity and drainage coefficient, downstream splash, sediment concentration and soil loss and with r = -0.976, 0.927 and -0.927 between initial soil moisture content and time-to-runoff, runoff coefficient, respectively.

Key words: mulch, organic amendment, soil and water conservation, soil moisture, splash erosion

INTRODUCTION

Soil erosion due to water and wind results in the loss of valuable top soil and causes land degradation as well as environmental quality, water management and hydro-technical problems [BANASIK *et al.* 2012; BANASIK, MITCHELL 2008; BĄK, DĄBKOWSKI 2013; BHATTARAI *et al.* 2011; BOUCHELKIA *et al.* 2014; KOWALCZYK, TWARDY 2012; MIODUSZEWSKI 2012; MITCHELL *et al.* 2001]. There are different methods for soil conservation but biological methods in bare or degraded slopes need long time for establishment [ADEKALU *et al.* 2007; CERDÀ 1999; SMETS *et al.* 2008a; SPALEVIC *et al.* 2014]. Mulching the soil surface with a layer of plant residue is an effective method of conserving water and soil because it reduces surface runoff, increases infiltration of water into the soil and retard soil erosion [ADEKALU *et al.* 2007;



KARABOVA et al. 2012; MORGAN 2004; POESEN, LAVEE 1991; WU et al. 2012]. Organic mulches can be used to protect quickly, when plants cannot be established, the soil surface against the erosive forces of rain and runoff [GHOLAMI et al. 2013; SMETS et al. 2008b]. Straw mulch of the remaining plants has been used to reduce evaporation and to modify soil and soil aggregates [ADAMS 1966; KUKAL, SARKAR 2010]. Several studies have shown the importance of soil organic matter content in retard time of initial runoff [GHOLAMI et al. 2013; LEE et al. 2012], increasing infiltration (e.g. DULEY, KELLY [1939]; GILLEY et al. [1986]), runoff reduction and soil erosion control [AUERSWALD et al. 2003; GHOLAMI et al. 2013]. The straw mulches can absorb the impact of raindrops [ADEKALU et al. 2007; GHOLAMI et al. 2013; KUKAL, SARKAR 2010; LAL 1976] and reduce the detachment of soil aggregates [ADEKALU et al. 2007; GHOLAMI et al. 2013; KUKAL, SARKAR 2010].

Describing the relationship between rainfall, infiltration, and runoff through rainfall simulation in laboratorial conditions were conducted in previous researches [GRACE et al. 1998; WILSON et al. 2004] and field [MULUMBA, LAL 2008]. MANNERING and MEYER [1963] studied the effects of six rates of surface wheat mulch on infiltration and erosion. The mulching indicated that, it could reduce soil surface sealing as evidenced by higher infiltration rates and decrease rainfall and runoff energy for particle detachment and transport as evidenced by reduced soil content in the runoff. ADAMS [1966] studied influence of rice straw mulch on runoff, erosion and soil moisture depletion in 0.4 m² plots on a 4% slope in Texas. He observed that the straw mulch could reduce runoff and erosion. He also found that, this mulch significantly increased the infiltration of clay pan soils on sloping land. LAL [1976] used the rice straw with cover of 60 and 90% in the higher intensity for loamy-sand, sandy-loam and sandy-clay-loam soils. The amount of soil erosion reduced by 70, 86 and 81%, respectively, with 60%, while with cover of 90% mulch gave an average reduction of 94, 91 and 86%, respectively.

According to previous studies, the infiltration rate and the rapid movement of infiltrated water increased due to the use of straw mulch [ADAMS 1966]. The straw mulch also increased protection of the immediate soil surface due to absorption of water and the holding excess surface water of soil surface by mechanical impedance [ADAMS 1966].

According to GILLEY *et al.* [1986], sorghum mulch was more effective to reduce runoff coefficient compare with soybean and sorghum residue [SMETS *et al.* 2008a]. KHAN *et al.* [1988] investigated the influence of rice straw mulch on soil loss in the laboratory condition and showed that runoff and soil loss were significantly reduced with increasing mulch cover. They also showed that when the soil was wet, runoff was not affected by rainfall intensity and duration, slope of the plot and canopy cover variables except

for the mulch cover. LAL [1998] investigated that reductions in soil erosion by mulching were due both to decreased runoff and to lower sediment concentration in runoff. POULENARD et al. [2001] studied the infiltration, runoff and soil erosion under rainfall simulation for the *páramos* in Colombia effect of tillage and burning at plot scale. The results showed that the infiltration rate was very high and sediment loss was very low. Results indicated that land use change on páramos increased runoff flow and sediment losses from natural undisturbed páramos were very low. ADEKALU et al. [2007] also investigated Pennisetum purpureum mulching effect in three agricultural soils in Nigeria for two slopes. Runoff and soil loss decreased with mulch used and increased with slope. But in the highest cover, infiltration was increased and soil loss was reduced. MULUMBA and LAL [2008] studied mulching effects with wheat straw mulch at plot scale and the Waterman Farm of the Ohio State University, Columbus, on selected soil physical properties. The results demonstrated that mulch rates significantly increased available water capacity by 18-35% and soil moisture retention at low suctions from 29 to 70%. JORDÁN et al. [2010] checked the effect of mulching wheat straw on infiltration and runoff under semi-arid conditions in southern Spain. They found that the mulch layer contributed to increase the roughness and the interception of raindrops, delaying runoff generation, enhancing infiltration of rainwater and decreasing erosive responses during storms. Also they showed that, the delay of runoff flow enhanced the infiltration of rain water during storms. KUKAL and SARKAR [2010] also studied the effect of wheat straw mulch on splash erosion and infiltration rate in two soils under simulated rainfall in semi-arid tropics. The result showed that the effect of mulch in decreasing splash and increasing infiltration was more effective in sandy loam than in silt loam. PARLAK and ÖZASLAN PARLAK [2010] measured the splash erosion in vetch, barley and ryegrass cover crops for two slopes of 4 and 9% with three replications in Turkey. Splash erosion decreased with the increase in cover percentage and the decrease in the slope. GHAHRA-MANI et al. [2011] studied effect of ground cover on splash and sheetwash erosion over a steep forested hillslope in the scale plot. They showed that soil splash transport occurred in hillslopes with sparse understory vegetation, the contribution of splash transport to total sediment movement depended on vegetation and the ground cover controlled the infiltration capacity and overland runoff depth by developing a litter layer and macropores in surface soil. LI et al. [2011] studied effects of bahia grass mulch on runoff and sediment yield of sloping red soil at 15×5 m plot scale in Southern China. They found that the straw mulch increased infiltration and reduced significantly runoff and sediment yield.

Annual runoff reduction ratio of 26.9% due to the use of straw mulch was reported by CHOI *et al.* [2012]. LEE *et al.* [2012] used from straw mat, PAM

(Soilfix G1, Ciba Chemical Co., Germany), rice chaff, sawdust, and gypsum for reduction of soil erosion under 10 and 20% slopes and 30 $\text{mm}{\cdot}\text{h}^{-1}$ rainfall simulation in Korea. The average reduction of runoff under 10 and 20% slopes was 85.6% and 72.0%, respectively. The average reduction of sediment discharge from mulched plots was 99%. Also in this study infiltration increased and retard time of initial runoff. LIU et al. [2012] evaluated the effect of rice straw mulch for plot scale and 2 years in the Xiaofuling watershed in the Danjiangkou Reservoir area. The straw mulch treatment significantly decreased the runoff and the sediment yield from 18 up 22% and also infiltration increased. GHOLAMI et al. [2013] studied straw mulching effect on splash erosion, runoff and soil loss from eroded plots with simulated rainfall intensities of 30, 50, 70, and 90 mm $\cdot h^{-1}$ and a slope of 30% and three replicates in Iran. The data from splash cups showed that, the maximum splash reduction occurring at a rainfall intensity of 70 $mm \cdot h^{-1}$. The results of the research also showed that the straw mulch had a significant effect in changing runoff and soil erosion characteristics at a confidence level of 99%. SHI et al. [2013] studied effects of mulch cover rates of 0, 15, 30, 50, 70, and 90% cover using simulated rainfall on runoff and erosion processes in 15% slope. The results showed that, mulch rates reduced the runoff coefficient values and soil loss when compared with the bare soil case. Also mulch rate of 90% had the most effect on processes.

Reviewing of literatures clearly verified the variability of hydrological responses and effectiveness of different mulches which emphasized further studies under different conditions. A few studies have been done to study the effects of straw mulch on infiltration, runoff, soil loss and especially splash erosion in different soils. The present study has been therefore conducted to study the efficiency of straw mulch on splash erosion, time-to-runoff, runoff coefficient, infiltration, drainage, sediment concentration and soil loss for a sandy-loam soil taken from deforested area, about 15 km of Warsaw west, Poland. The study has been done under lab conditions with simulated rainfall intensities of 60 and 120 mm·h⁻¹, soil moisture of 12, 25, 33 and 40 volumetric percent and the slope of 9%.

METHODS

RAINFALL SIMULATOR

The experiments were checked the effect of barley straw mulch as conservation soil on bare soil. These were done by using simulated rainfall in intensities of 60 and 120 mm·h⁻¹ at 4 soil moistures of 12, 25, 33 and 40% on infiltration, time-to-runoff, runoff amount, splash erosion and sediment yield. The rainfall simulator lab consisted of a 10 L water reservoir and 3 nozzles (BEX: 3/8 S24W).

SOIL CHARACTERISTICS AND PREPARATION

Soil was collected from the top layer of 0-50 cm [KUKAL, SARKAR 2010] about 15 km of Warsaw west, Poland. Then soil was carried to WULS-SGGW laboratory and initial experiments were performed on that. The soil texture was of sandy-loam (12.6% clay, 30.8% silt and 56.6% sand). Also the experimented soil of bulk density, pH, EC and organic matter were 1.67 g·cm⁻³, 6.73, 124 μ mohs·cm⁻¹ and 2.76%, respectively. The KUKAL and SARKAR [2011] method was used as basic method for preparation of soil. At first collected soil were transferred to lab and air-dried up to optimum moisture content to maintain the relative stability of soil aggregates [KUKAL, SARKAR 2011], then pebbles and plant debris were removed through passing a 4 mm sieve [TANG et al. 2006] to increase the homogeneity of soil layers [AGASSI, BRADFORD 1999; DEFERSHA et al. 2011].

EROSION PLOT

The laboratory works were conducted using one 2 m² erosion plot, the slope of 9% [PARLAK, ÖZA-SLAN PARLAK 2010] and also those carried out in the Warsaw University of Life Sciences (WULS), Poland. A splash cup proposed by MORGAN [1978] was used for measurement of splash erosion. A 2.5 cm layer of artificial pumice grain was covered by a layer of 2.5 cm sand with total thickness of 5 cm as a filter layer under the experimented soil for the creation of infiltration layer [DARBOUX et al. 2001; DEFERSHA et al. 2011; GHOLAMI et al. 2013]. A 7 cm-thick soil as top layer was compacted by PVC roller (filled with cement and sand) to achieve the bulk density of 1.67 g·cm⁻³ almost equal to the originated soil under natural conditions [GHOLAMI et al. 2013; ROMKENS et al. 2001].

BARLEY STRAW MULCH

To achieve the study purpose, the soil surface was covered by the air-dried barley straw [PARLAK, PARLAK 2010] with the surface coverage of about 90% [ADEKALU *et al.* 2007; LAL 1976; SHI *et al.* 2013] and dry weight of 350 g m⁻² (Phot. 1). The control plot was monitored under identical lab conditions on bare soils and just before applying the straw mulch.

LABORATORIAL MEASUREMENTS

Each run was conducted using new soil and straw mulch [ADEKALU *et al.* 2007]. For performance of experiments, a plot had the same primary conditions and also soil surface cover, which controls the detachment and transport of sediment [GHAHRAMANI *et al.* 2011; GHOLAMI *et al.* 2013], infiltration [ADEKA-LU *et al.* 2007; CHOI *et al.* 2012; LEE *et al.* 2012] and the generation of runoff [GHAHRAMANI *et al.* 2011; GHOLAMI *et al.* 2013].



Phot. 1. Treated plot with barley straw mulch (left) and illustration from treated splash cup (right); source: own

Splash erosion

A splash cup [MORGAN 1978] was used to measure splash erosion (Fig. 1). The splashed soil particles have been collected separately from upward and downward segments of cup after each experiment and measured using decantation procedure and oven drying at 105°C for 24 h and weighed by means of highprecision scales [WALLING *et al.* 2001].

• Runoff

Time-to-runoff was recorded as the time-toarriving the first drop of runoff to plot outlet. The 2 minutes intervals [RUIZ-SINOGA *et al.* 2010] were then considered for collecting runoff volumes in plot outlet for all experiments.

• Infiltration and drainage

The volume of the infiltrated water was calculated in 2 minutes intervals as the difference between the volume of water rained and the runoff volume [ADEKALU *et al.* 2007]. For the first interval, the difference between dry-weight and wet-weight of the straw mulch was also measured to increase the accuracy of calculations [ADEKALU *et al.* 2007; LI *et al.* 2011]. Time-to-drainage was recorded as the time-toarriving the first drop of drained water to plot drainage outlet. All drained waters were then collected to determine the drainage coefficient.

Sediment concentration and soil loss

The sediment concentration in each runoff sample was measured using decantation procedure and oven drying at 105°C for 24 h and weighing by means of high-precision scales [WALLING *et al.* 2001]. The soil loss was finally calculated as the total dryweighted sediment losses from plot in each experiment by adding the results of multiplying sediment concentration and runoff volume in all 2 minutes intervals.

RESULTS AND DISCUSSION

• Splash erosion

The results of splash erosion in all experiments are shown in Table 1. The interactions between soil moisture and rainfall intensity on splash erosion are shown in Figure 1.

Table 1. Splash erosion $(g \cdot m^{-2})$ for all experiments

Initial soil moisture %	Rainfall intensity mm h ⁻¹	Control	Treated	Conservation ratio %
12		20.55	13.04	-36.52
25	60	23.70	17.39	-26.63
33		31.52	23.97	-23.96
40		35.67	25.48	-28.57
12	120	64.81	26.85	-58.57
25		74.61	32.89	-55.92
33		89.50	36.42	-59.31
40		92.99	49.68	-46.58

Source: own study.



Fig. 1. Relationship between initial soil moisture and splash erosion in various rainfall intensities before (blank symbols) and after (solid symbols) straw mulching; source: own study

According to Table 1 and Figure 1, the minimum conservation ratio of straw mulch on splash erosion (23.96%) was in the soil moisture of 33% and the rainfall intensity of 60 mm·h⁻¹ while the maximum conservation ratio of straw mulch was in the soil moisture of 33% and the rainfall intensity of 120 mm·h⁻¹. The results were in agreement with the previous studies (e.g. GHOLAMI *et al.* [2013]) which confirmed the conservation effects of straw mulch on splash erosion in various rainfall intensities and initial soil moistures and confirmed more conservation effect in higher rainfall intensities. Figure 1 showed the linear relationship ($R^2 \ge 0.93$) between splash erosion and initial soil moisture in various rainfall intensities.

The straw mulch can intercept raindrop impact on soil surface and also maintained soil surface structure [ADAMS 1966; GHOLAMI et al. 2013; POESEN, LAVEE 1991]. In agreement with KUKAL and SARKAR [2010], the results showed that the straw mulch reduces raindrop impacts on soil surface and then eliminates splash erosion. In other words, the results verified that the straw mulch protects soil aggregates from direct impact energy of raindrops and prevents soil detachment [GHOLAMI et al. 2013; JORDÁN et al. 2010; KU-KAL, SARKAR 2010] and also increases the roughness of soil surface [GHOLAMI et al. 2013]. The conservative effects of straw mulch on soil splash was more significant at higher rainfall intensities than the lowers, because of physically protecting effect of straw mulch in soil surface against raindrop impacts specially in high rainfall intensities [ADAMS 1966]. The conservation ratio of straw mulch in splash erosion was decreased with increasing rainfall intensity and soil moisture, because of reducing the resistance of soil aggregates against the raindrops in near saturated

or saturated conditions. The amount of bare soil particles in contact with raindrops decreased with straw mulch and consequently, soil particles splash and transport were decreased [GHOLAMI *et al.* 2013; KHAN *et al.* 1988].

• Runoff

The time-to-runoff and runoff coefficient before and after straw mulching are shown in Table 2. The relationships between initial soil moisture and timeto-runoff are shown in Figure 2a and runoff coefficient in Figure 2b in various rainfall intensities before (blank symbols) and after (solid symbols) straw mulching.

The results of Table 2 showed that the time-torunoff and the runoff coefficient increased and decreased, respectively after straw mulching, due to the ability of straw mulch pieces to store a significant amount of runoff and increase infiltration [CHOI *et al.* 2012; DULEY, KELLY 1939; GHOLAMI *et al.* 2013; LIU *et al.* 2012; POESEN, LAVEE 1991].

Initial soil	Rainfall intensity mm·h ⁻¹		Time-to-rur	noff, s	Runoff coefficient, %			
moisture %		control	treated	enhancement ratio %	control	treated	conservation ratio %	
12		285	579	103.16	11.68	4.30	-63.18	
25	60	89	158	77.53	53.39	32.98	-38.23	
33		33	77	133.33	64.42	45.79	-28.92	
40		24	68	183.33	68.99	55.08	-20.16	
12		184	408	121.74	31.05	12.73	-59.00	
25	120	64	214	234.38	56.26	50.88	-9.56	
33		23	80	247.83	68.19	51.95	-23.82	
40		14	67	378.57	77.56	58.11	-25.08	

Table 2. Time-to-runoff and runoff coefficient for all experiments

Source: own study.



Fig. 2. Relationship between initial soil moisture and time-to-runoff (a) and runoff coefficient (b) in various rainfall intensities before (blank symbols) and after (solid symbols) straw mulching; source: own study

Although the runoff depend on the straw mulching [JORDÁN *et al.* 2010], but the rate of changes were different in various rainfall intensities and initial soil moisture contents. The maximum enhancement ratio of time-to-runoff due to straw mulch in both rainfall intensities of 60 and 120 mm h^{-1} was in the initial soil moisture of 40% (Tab. 2).

The results showed that in all studied rainfall intensities and initial soil moistures contents, the runoff coefficient reduced due to straw mulching. The maximum enhancement ratio of runoff coefficient due to straw mulch in both rainfall intensities of 60 and 120 $\text{mm}\cdot\text{h}^{-1}$ was in the initial soil moisture of 12%. It might be due to water absorbing effects of straws. The results were in the same line with those reported by DULEY and KELLY [1939], LAL [1976] and POESEN and LAVEE [1991] (Tab. 2).

The results presented in Figure 2 showed that the relationships between initial soil moisture and timeto-runoff (a) in all treatments were exponential while the relationships between initial soil moisture and runoff coefficient (b) in all treatments were logarithmic. A similar nonlinear relationships have been reported by SMETS *et al.* [2008a] for treated plots by different soil surface covers. GHOLAMI *et al.* [2013] also showed that the relationship between runoff coefficient and rainfall intensity in mulch treated plot is logarithmic.

According to the results, it seems that, in agreement with KHAN *et al.* [1988], in high levels of initial soil moisture contents, runoff was more affected by mulch cover.

• Infiltration and drainage

The results of infiltration and drainage coefficient are showed in Table 3 and the interactions between initial soil moisture and rainfall intensity on infiltration and drainage coefficient in control and treated plots are showed in Figure 3.

The results in Table 3 showed that the straw mulch increased the infiltration with the enhancement ratio from 4.59 to 78.61% in various treatments. Although the time-to-drainage reduced and drainage coefficient increased due to straw mulch effects on infiltration in all studied treatments, the enhancement ratio in drainage coefficient in the rainfall intensity of 60 mm·h⁻¹ was more than the 120 mm·h⁻¹. Figure 3 shows the effects of initial soil moisture on infiltration coefficient, time-to-drainage and drainage coefficient before and after straw mulch in both rainfall intensities. The interaction of initial soil moisture and rainfall intensities. The interaction of initial soil moisture and rainfall intensities was poor (Fig. 3).

The maximum increasing effects of straw mulch on infiltration coefficient appeared in higher intensity and soil moisture. The maximum effects of straw mulch on infiltration in higher rainfall intensity and higher initial soil moisture content was in agreement with ADAMS [1966] and MULUMBA and LAL [2008], respectively. The results also verified a large enhancement in the drainage coefficient after treated treatments due to straw mulch.

Table 3. Infiltration coefficient, time-to-drainage and drainage coefficient for all experiments

Initial soil Rainfall		Infiltration coefficient, %			Т	Time-to-drainage, s			Drainage coefficient, %		
moisture %	intensity mm·h ⁻¹	control	treated	enhancement ratio %	control	treated	conservation ratio %	control	treated	enhancement ratio %	
12		88.32	92.37	4.59	974	631	-35.22	27.32	62.35	128.22	
25	60	46.61	63.95	37.20	685	275	-59.85	32.18	66.34	106.15	
33	00	35.58	51.27	44.10	634	203	-67.98	25.18	66.12	162.59	
40		31.01	41.29	33.15	1090	367	-66.33	20.49	54.57	166.33	
12		68.95	85.55	24.08	565	418	-26.02	30.26	44.69	47.69	
25	120	43.74	47.50	8.60	382	291	-23.82	25.58	48.57	89.87	
33	120	31.81	46.15	45.08	697	274	-60.69	26.34	36.16	37.28	
40		22.44	40.08	78.61	1393	291	-79.11	16.60	30.74	85.18	

Source: own study.



Fig. 3. Relationships between initial soil moisture and infiltration coefficient (a) and drainage coefficient (b) in various rainfall intensities before (blank symbols) and after (solid symbols) straw mulching; source: own study

Straw mulch operated physical barrier against runoff moving and let it more time to infiltrate into the soil surface [JORDÁN *et al.* 2010].

• Sediment

The sediment concentration and soil loss amounts before and after straw mulch are shown in Table 4. Figure 4 shows the interaction between initial soil moisture and rainfall intensity on sediment concentration (a) and soil loss (b) before and after straw mulching.

The results of Table 4 and Figure 4 showed that soil loss reduced due to the conservation treatment

with straw mulch which is in agreement with previous researches vis. ADAMS [1966] and POESEN and LAVEE [1991]. The results indicates that there is no enough power runoff flow to detach or transport particles which is in agreement with MANNERING and MEYER [1963], LAL [1998] and GHOLAMI *et al.* [2013].

Figure 4 shows that the relationship between initial soil moisture and sediment concentration (a) and soil loss (b) were linear ($R^2 \ge 0.52$ and 0.65, respectively). The conservation ratios of straw mulch on sediment concentration were from 71.14 to 91.55%, while for soil losses were from 75.89 to 94.22%.

Soil moisture	Rainfall intensity	Sec	liment concentr	ation, $g \cdot l^{-1}$	Soil loss, g			
%	mm·h ⁻¹	control	treated	conservation ratio %	control	treated	conservation ratio %	
12		1.22	0.35	-71.31	6.04	0.44	-92.72	
25	60	2.30	0.27	-88.26	37.23	2.31	-93.80	
33		4.23	0.36	-91.49	78.25	4.53	-94.21	
40		4.09	0.50	-87.78	81.41	7.72	-90.52	
12		3.14	0.80	-74.52	59.26	5.92	-90.01	
25	120	3.76	1.03	-72.61	127.40	30.72	-75.89	
33		3.94	1.14	-71.07	155.42	34.42	-77.85	
40		4.35	1.03	-76.32	192.53	32.66	-83.04	

Table 4. Sediment concentration and soil loss for all experiments

Source: own study.



Fig. 4. Relationship between initial soil moisture and sediment concentration (a) and soil loss (b) in various rainfall intensities before (blank symbols) and after (solid symbols) straw mulching; source: own study

• Statistical analysis

Because of nonlinear relationships and nonnormal data, the Spearman-Rho correlation coefficient was used to estimate correlations between the quantitative characteristics of splash, runoff, infiltration, sediment concentration and soil loss [SEEGER 2007]. Tables 5 and 6 shows the results of Spearman-Rho correlations and Paired Samples T-test, respectively. The results of statistical analysis showed the significant ($p \le 0.05$) Spearman-Rho correlation coefficients of -0.873, 0.873, 0.878 and 0.764 between rainfall intensity and drainage coefficient, downstream splash, sediment concentration and soil loss and also -0.976, 0.927 and -0.927 between initial soil moisture content and time-to-runoff, runoff coefficient and infiltration coefficient, respectively (Tab. 5). According to Table 6, there are significant differences between studied parameters due to straw mulching.

Factors	Rainfall intensity mm·h ⁻¹	Initial soil moisture %	Time-to- runoff s	Runoff coeffi- cient %	Infiltra- tion coef- ficient %	Time-to- drainage s	Drainage coeffi- cient %	Down- stream splash g·m ⁻²	Sediment concentration $g \cdot l^{-1}$	Soil loss g
Rainfall intensity, mm·h ⁻¹	1									
Initial soil moisture, %	0	1								
Time-to-runoff, s	0	-0.976**	1							
Runoff coefficient, %	0.327	0.927**	-0.881**	1						
Infiltration coefficient, %	-0.327	-0.927**	0.881**	-1.000**	1					
Time-to-drainage, s	0	-0.442	0.491	-0.347	0.347	1				
Drainage coefficient, %	-0.873**	-0.293	0.262	-0.548	0.548	-0.132	1			
Splash, g·m ^{−2}	0.873**	0.488	-0.476	0.738*	-0.738*	-0.216	-0.905**	1		
Sediment concentration, g·l ⁻¹	0.878**	0.344	-0.275	0.611	-0.611	-0.157	-0.898**	0.934**	1	
Soil loss, g	0.764*	0.586	-0.524	.810*	-0.810*	-0.299	-0.833*	0.952**	0.946**	1

Table 5. Spearman-Rho coefficient between different studied factors

Source: own study.

Table 6. Results of Paired Samples *T*-test for studied factors before and after straw mulching

	95% confidence interval of the difference									
Item	mean	standard deviation	standard error mean	lower	upper	Т	DF	sig. (2-tailed)		
Time-to-runoff, s	-116.875	96.010	33.945	-197.141	-36.609	-3.443	7	0.011		
Runoff coefficient, %	14.965	5.690	2.012	10.208	19.722	7.440	7	0.000		
Infiltration coefficient, %	-12.463	5.768	2.039	-17.285	-7.640	-6.111	7	0.000		
Time-to-drainage, s	458.750	323.783	114.475	188.060	729.440	4.007	7	0.005		
Drainage coefficient, %	-25.699	11.840	4.186	-35.597	-15.800	-6.139	7	0.000		
Splash, $g \cdot m^{-2}$	25.954	19.796	6.999	9.404	42.503	3.708	7	0.008		
Sediment concentration, $g \cdot l^{-1}$	2.694	0.962	0.340	1.889	3.498	7.917	7	0.000		
Soil loss, g	77.353	48.756	17.238	36.592	118.113	4.487	7	0.003		

Explanations: T – t-statistic value, DF – degrees of freedom, sig. – statistical significance (p-value). Source: own study.

CONCLUSIONS

The present study was conducted in plot scale and laboratory conditions to determine the efficiency of 350 g·m⁻² straw mulch in splash erosion, runoff, infiltration, sediment concentration and soil loss under simulated rainfall intensities of 60 and 120 mm·h⁻¹, 4 soil moistures of 12, 25, 33 and 40% and the constant slope of 9%. A sandy-loam soil originated from about 15 km Warsaw west, Poland. The results verified the significant conservation abilities of straw mulch to reduce splash erosion, soil sealing, runoff, sediment concentration and soil loss and increase infiltration and drainage rates.

Acknowledgement

The authors would like to thank to Drs Andrzej Brandyk, Anna Baryła, Dariusz Górski and Ms Marta Mackiewicz for their assistance to coordinate cooperation with Water Centre Laboratory, to Zygmunt Pietraszek for his technical assistance with the nozzles and rainfall simulations and to Jacek Gladecki for his ongoing assistance with preparation of soil and other materials in laboratory. The laboratory investigations have been conducted in Water Center Laboratory of Warsaw University of Life Sciences – SGGW, during 6-month research stay of Leila Gholami and Abdulvahed Khaledi Darvishan at Department of Water Engineering of Warsaw University of Life Sciences – SGGW, and have been partly supported by PL-NCN as part of research project nr: NN305 396238. The support provided by the organization is gratefully acknowledged.

REFERENCES

- ADAMS J.E. 1966. Influence of mulches on runoff, erosion and soil moisture depletion. Soil Science Society of America Journal. No 30(1) p. 110–114.
- ADEKALU K.O., OLORUNFEMI I.A., OSUNBITAN J.A. 2007. Grass mulching effect on infiltration, surface runoff and soil loss of three agricultural soils in Nigeria. Bioresource Technology. Vol. 98(4) p. 912–917.
- AGASSI M., BRADFORD J.M. 1999. Methodologies for interrill soil erosion studies. Soil and Tillage Research. No 49 p. 277–287.
- AUERSWALD K., KAINZ M., FIENER P. 2003. Soil erosion potential of organic versus conventional farming evaluated by USLE modeling of cropping statistics for agricultural districts in Bavaria. Soil Use Management. No 19 p. 305– 311.
- BANASIK K., MITCHELL J.K. 2008. Conceptual model of sedimentgraph from flood events in a small agricultural watershed. Annals of Warsaw University of Life Sciences – SGGW. Land Reclamation. No 39 p. 49–57.
- BANASIK K., GÓRSKI D., POPEK Z., HEJDUK L. 2012. Estimating the annual sediment yield of a small agricultural catchment in central Poland. In: Erosion and sediment yields in the changing environment. Eds. A.E. Collins, V. Golosov, A.J. Horowitz, X.Ju.M. Stone, D.E. Walling,

X. Zhang. IAHS Publications. No 356. Wallingford. IAHS Press p. 267–275.

- BĄK Ł., DĄBKOWSKI SZ.L. 2013. Spatial distribution of sediments in Suchedniow reservoir. Journal of Water and Land Development. No 19 p. 13–22.
- BHATTARAI R., KALITA P.K., YATSU S., HOWARD H.R., SVENDSEN N.G. 2011. Evaluation of compost blankets for erosion control from disturbed lands. Journal of Environmental Management. Vol. 92(3) p. 803–812.
- BOUCHELKIA H., BELARBI F., REMINI B. 2014. Quantification of suspended sediment load by double correlation in the watershed of Chellif (Algeria). Journal of Water and Land Development. No 21 p. 39–46.
- CERDÀ A. 1999. Parent material and vegetation affect soil erosion in eastern Spain. Soil Science Society of America Journal. No 63 p. 362–368.
- CHOI J., SHIN M.H., YOON J.S., JANG J.R. 2012. Effect of rice straw mulch on runoff and NPS pollution discharges from a vegetable field. In: Soil and water engineering. International Conference of Agricultural Engineering – CIGR – AgEng 2012: Agriculture and engineering for healthier live. Valencia, Spain, July 8–12. p. 4.
- DARBOUX F., DAVY P.H., GASCUELODOUX C., HUNG C. 2001. Evolution of soil surface roughness and flowpath connectivity in overland flow experiments. Catena. No 46 p. 125–139.
- DEFERSHA M.B., QURAISHI S., MELLESE A.M. 2011. The effect of slope steepness and antecedent moisture content on interrill erosion, runoff and sediment size distribution in the highlands of Ethiopia. Hydrology and Earth System Sciences. No 15 p. 2367–2375.
- DULEY L., KELLY L.L. 1939. Effect of soil type, slope and surface conditions on intake of water. Nebraska Agricultural Experiment Station Research Bulletin. No 112 p. 16.
- GHAHRAMANI A., ISHIKAWA Y., GOMI T., KATSUSHIGE SH., MIYATA SH. 2011. Effect of ground cover on splash and sheetwash erosion over a steep forested hillslope: a plotscale study. Catena. No 85 p. 34–47.
- GHOLAMI L., SADEGHI S.H.R., HOMAEE M. 2013. Straw mulching effect on splash erosion, runoff and sediment yield from eroded plots. Soil Science Society of America Journal. No 77 p. 268–278.
- GILLEY J.E., FINKNER S.C., VARVEL G.E. 1986. Runoff and erosion as affected by sorghum and soybean residue. Transactions of the American Society of Agricultural Engineers. No 29 p. 1605–1610.
- GRACE J.M., RUMMERM B., STOKES B.J., WILHOIT J. 1998. Evaluation of erosion control techniques on forest roads. Transactions of the American Society of Agricultural Engineers. No 41(2) p. 383–391.
- JORDÁN A., ZAVALA L.M., GIL J. 2010. Effects of mulching on soil physical properties and runoff under semi-arid conditions in southern Spain. Catena. No 81 p. 77–85.
- KARABOVA B., SIKORSKA A.E., BANASIK K., KOHNOVA S. 2012. Parameters determination of a conceptual rainfallrunoff model for a small catchment in Carpathians. Annals of Warsaw University of Life Sciences – SGGW. Land Reclamation. No 44(2) p. 155–162.
- KHAN M.J., MONKE E.J., FOSTER G.R. 1988. Mulch cover and canopy effect on soil loss. Transactions of the American Society of Agricultural Engineers. No 31 p. 706–711.
- KOWALCZYK A., TWARDY S. 2012. Wielkość erozji wodnej obliczona metodą USLE [Comparison of the water erosion magnitude estimated by the modified USLE method]. Woda-Środowisko-Obszary Wiejskie. T. 12. Z. 1 p. 83–92.

- KUKAL S.S., SARKAR M. 2010. Splash erosion and infiltration in relation to mulching and polyviny alcohol application in semi-arid tropics. Archives of Agronomy and Soil Science. No 56(6) p. 697–705.
- KUKAL S.S., SARKAR M. 2011. Laboratory simulation studies on splash erosion and crusting in relation to surface roughness and raindrop size. Journal of the Indian Society of Soil Science. No 59(1) p. 87–93.
- LAL R. 1976. Soil erosion on alfisols in Western Nigeria II: Effect of mulch rates. Geoderma. No 16 p. 377–387.
- LAL R. 1998. Mulching effects on runoff, soil erosion and crop response on Alfisols in Western Nigeria. Journal of Sustainable Agriculture. No 11(2/3) p. 135–154.
- LEE S., WON C.H., SHIN M., PARK W., CHOI Y., SHIN J., CHOI J. 2012. Application of surface cover and soil amendment for reduction of soil erosion from sloping field in Korea. In: Soil and water engineering. International Conference of Agricultural Engineering – CIGR – AgEng 2012: Agriculture and engineering for healthier live. Valencia, Spain, July 8–12 p. 5.
- LI X.H., ZHANG Z.Y., YANG J., ZHAN, G.H., WANG B. 2011. Effects of Bahia grass cover and mulch on runoff and sediment yield of sloping red soil in Southern China. Pedosphere. No 21(2) p. 238–243.
- LIU Y., TAOA Y., WANA K.Y., ZHANGA G.S., LIUB D.B., XIONGB G.Y., CHENA F. 2012. Runoff and nutrient losses in citrus orchards on sloping land subjected to different surface mulching practices in the Danjiangkou Reservoir area of China. Agricultural Water Management. No 110 p. 34–40.
- MANNERING J.V., MEYER L.D. 1963. Effects of various rates of surface mulch on infiltration and erosion. Soil Science Society of American Journal. No 27 p. 84–86.
- MITCHELL J.K., BANASIK K., HIRSCHI M.C., COOKE R.A.C., KALITA P. 2001. There is not always surface runoff and sediment transport. In: Soil Erosion Research for the 21st Century. Proc. Int. Symp. Eds J.C. Ascough, D.C. Flanagan. St. Joseph, MI, USA, ASAE p. 676–678. doi: 10.13031/2013.4842.
- MIODUSZEWSKI W. 2012. Small water reservoirs their function and construction. Journal of Water and Land Development. No. 17 p. 45–52.
- MORGAN R.P.C. 1978. Field studies of rainsplash erosion. Earth Surface Processes and Landforms. No 3 p. 295– 299.
- MORGAN R.P.C. 2004. Soil erosion and conservation. 3rd ed. Longman Scientific and Technical, Burnt Mile, Harlow, UK. ISBN: 978-1-4051-1781-4 pp. 316.
- MULUMBA L.N., LAL R. 2008. Mulching effects on selected soil physical properties. Soil and Tillage Research. No 98 p. 106–111.
- PARLAK A., ÖZASLAN PARLAK A. 2010. Measurement of splash erosion in different cover crops. Turkish Journal of Field Crops. No 15(2) p. 169–173.
- POESEN J.W.A., LAVEE H. 1991. Effects of size and incorporation of synthetic mulch on runoff and sediment yield from interrills in a laboratory study with simulated rainfall. Soil and Tillage Research. No 21 p. 209–223.
- POULENARD J., PODWOJEWSKI P., JANEAU J.L., COLLINET J. 2001. Runoff and soil erosion under rainfall simulation of andisols from the ecuadorian paramo: effect of tillage and burning. Catena. No 45 p. 185–207.
- ROMKENS M.J.M., HELMING K., PRASAD S.N. 2001. Soil erosion under different rainfall intensities, surface roughness and soil water regimes. Catena. No 46 p. 103–123.
- RUIZ-SINOGA J.D., ROMERO-DIAZ A., FERRE-BUENO E., MAR-TÍNEZ-MURILLO J.F. 2010. The role of soil surface condi-

tions in regulating runoff and erosion processes on a metamorphic hillslope (southern Spain) soil surface conditions, runoff and erosion in southern Spain. Catena. No 80 p. 131–139.

- SEEGER M. 2007. Uncertainty of factors determining runoff and erosion processes as quantified by rainfall simulations. Catena. No 71 p. 56–67.
- SHI Z.H., YUE B.J., WANG L., FANG N.F., WANG D., WU F.Z. 2013. Effects of mulch cover rate on interrill erosion processes and the size selectivity of eroded sediment on steep slopes. Soil Science Society of America Journal. No 77 p. 257–267.
- SMETS T., POESEN J., BOCHET E. 2008a. Impact of plot length on the effectiveness of different soil-surface covers in reducing runoff and soil loss by water. Progress in Physical Geography. No 32(6) p. 654–677.
- SMETS T., POESEN J., KNAPEN A. 2008b. Spatial scale effects on the effectiveness of organic mulches in reducing soil erosion by water. Earth-Science Reviews. No 89 p. 1–12.
- SPALEVIC V., RAILIC B., DJEKOVIC V., ANDJELKOVIC A., CU-ROVIC M. 2014. Calculation of soil erosion intensity and

runoff of the Lapnjak watershed, Polimlje, Montenegro. Agriculture and Forestry. Vol. 60(2) p. 261–271.

- TANG Z., LEI T., YU J., SHAINBERG I., MAMEDOV A.I., BEN-HUR M., LEVY G.J. 2006. Runoff and interrill erosion in sodic soils treated with dry pam and phosphogypsum. Soil Science Society of America Journal. No 70(2) p. 679–690.
- WALLING D.E., COLLINS A.L., SICHINGABULA H.A., LEEKS G.J.L. 2001. Integrated assessment of catchment suspended sediment budgets: a Zambian example. Land Degradation and Development. No 12 p. 387–415.
- WILSON G.V., DABNEY S.M., MCGREGOR K.C., BARKOLL B.D. 2004. Tillage and residue effects on runoff and erosion dynamics. Transactions of the American Society of Agricultural Engineers. No 47(1) p. 119–128.
- WU L., LONG T.Y., LIU X., MMEREKI D. 2012. Simulation of soil loss processes based on rainfall runoff and the time factor of governance in the Jialing River Watershed, China. Environmental Monitoring and Assessment. Vol. 184(6) p. 3731–3748 doi: 10.1007/s10661-011-2220-6. Epub 2011 Jul 15.

Leila GHOLAMI, Kazimierz BANASIK, Seyed Hamidreza SADEGHI, Abdulvahed KHALEDI DARVISHAN, Leszek HEJDUK

Wpływ pokrycia gleby ściółką na infiltrację, erozję rozbryzgową, spływ i rumowisko określony w warunkach laboratoryjnych

STRESZCZENIE

Słowa kluczowe: *erozja rozbryzgowa, materiał organiczny, ochrona wody i gleby, ochronne działanie ściółki, wilgotność gleby*

Ściółka ze słomy może znacząco zmniejszać spływ powierzchniowy, powodując zwiększenie wsiąkania wody oraz zmniejszając erozję gleby. Ściółka jako materiał organiczny jest barierą redukującą także energię kinetyczną kropel deszczu, zmniejszając odspojenie i ograniczając transport agregatów glebowych. W prezentowanych badaniach podjęto próbę określenia wpływu ściółki ze słomy, jako środka ochronnego, na erozją rozbryzgową, czas do wystąpienia spływu, współczynnik spływu, koncentrację rumowiska i ilość zmywanej gleby. Doświadczenia laboratoryjne przeprowadzono w odniesieniu do piaszczystej gliny, pobranej z miejsca wylesionego, około 15 km na zachód od Warszawy, w symulowanych warunkach natężenia deszczu wynoszącego 60 i 120 mm·h⁻¹, wilgotności początkowej gleby 12, 25, 33 i 40% oraz spadku powierzchni 9%. Porównując te wyniki z wynikami doświadczenia przeprowadzonego w tych samych warunkach z glebą pozbawioną ściółki, wy-kazano znaczący wpływ redukujący w odniesieniu do erozji rozbryzgowej, współczynnika odpływu, koncentracji rumowiska i ilości zmywanej gleby oraz znaczący wpływ zwiększający wsiąkanie i odpływ podpowierzchniowy.